

## Accucappers HDEX & LD



### *Benefits and Features Include:*

- Hand Held
- Adjustable Clutch
- Forward and Reverse Rotation
- Quick Change of Chuck and Insert for Different Sized Caps
- Easy Torque Control
- Low Maintenance for long reliability
- Stand, Slide Rail, Self Balancer, are included.
- Comes with choice of one standard chuck and insert.

### **Electric Accucapper**

The Accucapper's are portable, hand-held, cap tighteners capable of tightening or removing screw and lug type caps. All Accucapper models have adjustable clutches to eliminate cap damage and reduce insert wear. Once the cap is tight the chuck automatically soaps spinning, signaling you to move on the next bottle. The included overhead slide rail with self-balancer

allows the Accucapper to be suspended neatly and weightless overhead, out of the way during case changes, reducing labor fatigue.

All Accucappers come complete with: one over-head slide rail, one self balancer, one chuck, and one rubber insert.

All of our equipment is manufactured on-site in Vista, California. Come and visit our showroom.

# MACHINE DIMENSIONS AND SPECIFICATIONS

AccuCappers	Machine Length	Machine Width	Machine Height
AccuCapper HDEX	12 "	2 "	2 "
AccuCapper LD	11 "	2 "	1.5 "
Electric AccuCapper	12 "	2 "	2 "

Net Weight (approx.)	Shipping Weight (approx.)
25	30 lbs

## ACCUCAPPER HDEX

Dimensions (Overall).....	2"W X 12"L 2"H.....	5 cm X 31 cm X 5 cm
Stand Dimensions.....	58"W X 61"H.....	147 cm X 155 cm
Net Weight (Approx.).....	22 lbs.....	10 Kg
Shipping Weight (Approx.).....	27 lbs.....	11 Kg
Operating Weight.....	0 lbs.....	0 Kg
Compressed Air Req.....	2.5 SCFM @ 100 PSI.....	2.4 LPS @ 6.9 BAR
Air Connection.....		1/4"/Male

## ACCUCAPPER LD

Dimensions (Overall).....	2"W X 12"L 2"H.....	5 cm X 31 cm X 5 cm
Stand Dimensions.....	58"W X 61"H.....	147 cm X 155 cm
Net Weight (Approx.).....	22 lbs.....	10 Kg
Shipping Weight (Approx.).....	27 lbs.....	11 Kg
Operating Weight.....	0 lbs.....	0 Kg
Compressed Air Req.....	2.5 SCFM @ 100 PSI.....	2.4 LPS @ 6.9 BAR
Air Connection.....		1/4"/Male

## ACCUCAPPER ELECTRIC

Dimensions (Overall).....	2"W X 12"L 2"H.....	5 cm X 31 cm X 5 cm
Stand Dimensions.....	58"W X 61"H.....	147 cm X 155 cm
Net Weight (Approx.).....	22 lbs.....	10 Kg
Shipping Weight (Approx.).....	27 lbs.....	11 Kg
Operating Weight.....	0 lbs.....	0 Kg
Compressed Air Req.....	2.5 SCFM @ 100 PSI.....	2.4 LPS @ 6.9 BAR
Electrical Required (Electric Accucapper).....		110 VAC 60 Hz 1 Phase
Electrical Usage.....		1 Amps

## TORQUE RANGE

MODEL	Maximum lb.
Electric AccuCapper	36
AccuCapper LD	35
AccuCapper HDEX	62

## CAPS SIZE TIGHTENING CAPABILITIES

MODEL	Millimeters
Electric AccuCapper	10mm-40mm
AccuCapper LD	5mm-25mm
AccuCapper HDEX	5mm-90mm

## CONTAINER SIZE

Minimum:  
Maximum:

## CAP TYPE

Screw and Lug

## CAPPING SPEED

## ELECTRIC STANDARD

100VAC - 5 AMPS

\*Electric Capper Only.

## ELECTRIC OPTIONAL

220VAC

\*Electric Capper Only

## COMPRESSED AIR REQ.

90PSI - 3 CFM

\*LD and HD Cappers